

ADMIRE PAINTS STAR PREMIUM EXTERIOR EMULSION PAINT

A High quality modified acrylic emulsion pigmented with titanium dioxide and other light fast and alkali resisting pigments. It has good flow and leveling and colour retention properties. It is an ideal smooth and matt coating for external areas.



admire
paints

KEY FEATURES

Application Type	- Exterior
Features	- Weather Resistant
Type	- Emulsion
Quantity	- 1, 4, 10 & 20 Litres
Colour	- White

PRODUCT DETAILS

Brand	- ADMIRE PAINTS
Model name	- Star Premium Emulsion
Suitable for	- Wall
Washable	- Yes
Life	- 2 Years

SPECIFICATION

Specific Gravity	- 1.45
Solids	- 58+/-1
Brookfield viscosity	- 110+/-10 cps
Dilution	- With water, 500 ml per litre
Finish	- Smooth
Surface drying time	- 30 Minutes
Setting time	- 24 Hours
Coverage	- 120+ Square feet per liter on Single coat, Depending upon Roughness and Porosity of the Wall.

APPLICATION METHOD

- 1** **CLEANING:** Prepare the surface by sanding with sand paper wipe clean.
- 2** **PRIMER:** Admire Paints Universal wall primer - Water Thinnable is to be thinned with water in the ratio 2:1 by volume to obtain brushing consistency. Apply a single coat and allow to dry for 3-4 hrs.
- 3** **PUTTY:** (Original) Smoothen surface by filling dents with coats of acrylic wall putty. Allow it to dry 4-6 hrs. Sand paper 180 wipe clean.
- 4** **EMULSION:** Admire paints Classic interior Emulsion or Star Premium Exterior Emulsion use after a coat of primer for good appearance. Allow it to dry for 3-4 hrs. Rub with sand paper 320 before application of top coat.



Exterior



Interior



Stir & Strain



Brush



Roll



Spray

STANDARD COLOUR COMPANY PVT LTD

Office : Old No 20, New No 41, Triplicane High Road,
Opp Walajah Big Masjid, Triplicane, Chennai - 600 005, Tamil Nadu, India

✉ info@admirepaints.com 🌐 www.admirepaints.com

Helpline Number : +91 (0) 44 48551431

Give Pride To Your Walls