



MULTI PURPOSE PREMIUM FLOOR AND WALL TILE ADHESIVE

BENEFITS

- Interior Floor & Wall Application
- For Ceramic Tiles, Semi-Vitreous Tiles, Precast Terrazzo & Small Natural Stones.
- Ready to use
- Excellent Bonding
- Moisture, Shock, Sag and Slump Resistant
- Easy to Use
- Self Curing
- Excellent Coverage
- Low Voc

SUBSTRATES

- Concrete
- Concrete Masonry
- Cement Plaster
- Brick Masonry
- Cement Terrazzo
- Ceramic Tile*
- Natural Stone*

* Ensure Surface is roughened and cleaned before use.



SPECIFICATIONS

Colour	Grey and White
Class	IS 15477:2019 - Type 1T Adhesive standards.
Coverage	Approx 3 Sqft/Kg for a 3 mm bed thickness using a square notched trowel.
Max Thickness	Upto 12mm
Mixing	5.5 - 6L Water for 20kg of Adhesive
Pot life	2-3 Hours
Open Time	10 Mins
Adjustment Time	10 Mins
Curing Time	24 Hours
Grouting	After 24 Hours.
Shelf Life	12 Months from the date of Manufacturing.
Packing	1kg, 5kg and 20kg