



# SUPER FLEXIBLE MULTIPURPOSE HIGH PERFORMANCE FLOOR AND WALL TILE ADHESIVE

## BENEFITS

- Interior and Exterior Floor and Wall Application • For Large Size Ceramic Tiles, Vitreous/Vitrified, Semi-Vitreous Tiles, Precast Terrazzo, Glass Mosaic Tiles, & Natural Stones.
- Suitable for Wet areas like Swimming Pools, Sauna, Water Tanks and Washrooms.
- Suitable for Wet on Wet and Tile on Tile application
- Ready to use
- Ultimate Bonding
- Highly Polymer Modified
- Moisture, Shock, Sag and Slump Resistant
- Easy to Use
- Self Curing
- Excellent Coverage
- Low Voc

## SUBSTRATES

- Concrete
- Cement Plaster
- Brick Masonry
- Cement Terrazzo
- All Types of Tiles and Natural Stones
- Cement Board
- Calcium Silicate Board
- Gypsum Board

## SPECIFICATIONS



Colour	Grey & White
Class	Exceeds IS 15477:2019 - Type 3 TS1 Adhesive standards.
Coverage	Approx 3 Sqft/Kg for a 3 mm bed thickness using a square notched trowel.
Max Thickness	Upto 12mm
Mixing	Grey : 5.5 - 6L, White : 6.0 - 6.5L for 20kg of Adhesive Powder.
Pot life	4 Hours
Open Time	30 Mins
Adjustment Time	30 Mins
Curing Time	24 Hours
Grouting	After 24 Hours.
Shelf Life	12 Months from the date of Manufacturing.
Packing	1kg, 5kg and 20kg