



READY TO USE CRACK FILLING PASTE FOR INTERNAL & EXTERNAL SURFACE CRACKS IN PLASTERS

BENEFITS

Ready to Use | Eco Friendly | Water Resistance | Shrink-Free | Excellent Bonding | High Elongation | Weather Durability
Slip Resistant | No Sagging | Paintable.

FEATURES

Appearance	Fine thick paste.
Colour	White
Shelf Life	12 Months from the date of Manufacturing.
Water Resistant	Excellent
Coverage	80-90 Running ft/Kg for plaster cracks with a depth of 5mm and width of 5mm.

AREAS OF APPLICATION

- For Internal and External Plastered walls having cracks upto 5mm width.

METHOD OF APPLICATION

- Clean the surface free from oil, dirt, grease, loose particles etc.
- Widen the hairline Cracks minimum upto 1mm.
- Existing POP or Putty must be removed thoroughly till the plaster surface is exposed.
- Apply Primer to porous surface using "CRACK-X SEAL 2001" mixed with water in 1:1 ratio.
- Do not allow the primer to dry completely and apply "CRACK-X SEAL 2001" & allow a setting time of 12 hrs before applying the 2nd coat.

CAUTION: • Should not be used for cracks more than 5mm thick. • Meant only for plaster cracks. Do not use for structural damages. • Not suitable for cracks in POP or Putty. • Do not apply during rain. • Drying time will be delayed for application below 10°C.