



Admire Paints ArtTex Texture Stucco Marble Finish is a specially formulated Special effects paint using a special grade natural Egyptian lime mineral. It is a hi-gloss ultra smooth plaster for Interior application giving various glossy marble finishes to egg-shell natural stone finishes depending on the tool used and the amount of time given for buffing.

BENEFITS

Ready To Use - Not to be Diluted | Suitable for Interior application | Ultra Smooth Tough Texture finish | Washable | Stain Resistant | Eco Friendly | Excellent Bonding | 2X Coverage

FEATURES

Finish	Marble, Slate, Quartz, Cobbled and more
Type	Natural Lime based mineral plaster
Drying Time	1st Coat : 6-8 hours, Second Coat : 2-3 hours, Third Coat : 45 to 60 minutes.
Colours	100+ Vibrant Colours can be tinted using the PS1 White Base Paint.
Packing	1Kg / 25kg Bucket
Coverage*	2 -2.5 Sq.m/ Kg per coat based on the pattern, tools and the surface condition.

APPLICATION

Clean the Surface through with 180 emery paper. Apply Admire Paints wall primer and allow it to dry for 3-4 hours. Smoothen the surface by applying 2-3 coats of Admire Paints ArtTex Acrylic Wall Putty giving 3-4 hours of drying time between each coat. Sand the surface with 180 emery paper and primer the surface again and allow it to dry for 3-4 hours. Apply 1st coat of ADMIRE Paints ArtTex Stucco Marble Texture Paint without dilution using a steel trowel and allow it to dry for 6-8 Hrs. Sand the surface with 180 Emery Paper and clean it thoroughly. Apply the 2nd coat of ADMIRE Paints ArtTex Stucco Marble Texture Paint without dilution using steel trowel and make the desired pattern and allow it to dry for 2-3 Hrs and sand the surface using 400 Emery Paper and buff the surface gently using a steel trowel.

Apply the 3rd coat of ADMIRE Paints ArtTex Stucco Marble Texture Paint without dilution using steel trowel and buff the surface depending on the desired Sheen level.

PRECAUTIONS: Do not apply when temperature below 10°C. Use of Stainers or colourants is not recommended. Thinning is not recommended. Do not keep material open for a long time. Product cannot be applied on surfaces/substrats that are subjected to continuous seepage or dampness. Stir well before use.

