



Admire Paints ArtTex Stucco Matt Texture Finish Paint is a specially formulated Special effects paint made using a special grade natural Egyptian lime mineral. It is a Egg Shell - Matte Finish super smooth plaster for Interior application giving various Egg Shell Matte Finish to Satin finish and Patterns depending on the procedure, tool used and the amount of time given for buffing.

BENEFITS

Ready To Use - Not to be Diluted | Suitable for Interior application | Ultra Smooth Tough Texture finish | Washable | Stain Resistant | Eco Friendly | Excellent Bonding | 2X Coverage

FEATURES

Finish	Marble, Slate, Quartz, Cobbled and more
Type	Natural Lime based mineral plaster
Drying Time	1st Coat : 6-8 hours, Second Coat : 2-3 hours, Third Coat : 45 to 60 minutes.
Colours	100+ Vibrant Colours can be tinted using the PS1 White Base Paint.
Packing	1Kg / 25kg Bucket
Coverage	2 -2.5 Sq.m/ Kg per coat based on the pattern, tools and the surface condition.

APPLICATION

Clean the Surface thoroughly with 180 grit emery paper. Apply Admire Paints CreteCare Wall Primer and allow it to dry for 3-4 hours. • Smoothen the surface by applying 2 coats of Admire Paints ArtTex Acrylic Wall Putty giving 3-4 hours of drying time between each coat. • Sand the surface with 180 grit emery paper and apply Admire Paints CreteCare Wall Primer and allow it to dry for 3-4 hours. • Apply 1st coat of ADMIRE Paints ArtTex Stucco Matt Texture Finish Paint without dilution using a Stainless steel trowel and allow it to dry for 6-8 Hrs. • Sand the surface with 180 grit emery paper and clean it thoroughly. • Apply the 2nd coat of ADMIRE Paints ArtTex Stucco Matt Texture Finish Paint without dilution using Stainless steel trowel and make the desired pattern and allow it to dry for 2-3 Hrs and sand the surface using 400 grit emery paper. • Apply the 3rd coat of ADMIRE Paints ArtTex Stucco Matt Texture Finish Paint without dilution using Stainless steel trowel to get the desired finish.

PRECAUTIONS: Do not apply when temperature below 10°C. Use of Stainers or colourants is not recommended. Thinning is not recommended. Do not keep material open for a long time. Product cannot be applied on surfaces/substrates that are subjected to continuous seepage or dampness. Stir well before use.

